

EXPANSION JOINT AT STRUCTURES, CURBS, WALLS. KEEP TOP OF JOINT FILLER BELOW PAVERS. CAULK AND SEAL AS NEEDED. MORTAR OR SAND JOINTS BRICK OR GRANITE PAVERS 3/4" SAND/ CEMENT (3:1) SETTING BED

REINFORCED CONCRETE SLAB

AGGREGATE SUB-BASE

UNDISTURBED OR COMPACTED SUBGRADE

PAVERS ON A RIGID BASE: SECTION

SCALE: 1"=1'-0"

## NOTE:

- 1. ON LOCUST WALK, USE 4" x 4" x 2-1/4" GRANITE SETTS SET WITH SAND JOINTS, 1/4" MIN. TO 1/2" MAX.
- GRANITE SETTS TO BE MOUNT AIRY, THERMAL FINISH TOP WITH SAWN SIDES AND BOTTOM, OR EQUAL

CSI 32 14 40 - 2
PAVERS ON RIGID BASE
LANDSCAPE STANDARDS

PRIOR TO CONSTRUCTION, CONFIRM LAYOUT, DIMENSIONS, ADJACENT UTILITIES AND FINAL MATERIALS WITH U OF P OFFICE OF THE UNIVERSITY ARCHITECT. THIS DETAIL TO BE USED AS A GUIDE ONLY. SPECIFIC REVISIONS FOR SITE CONDITIONS AND INTENT ARE THE RESPONSIBILITY OF THE INDIVIDUAL PROJECT DESIGNER.



Facilities & Real Estate Services Office of the University Architect 2023