

PRUNE ONLY BROKEN OR DEAD BRANCHES

THREE (3) GALVANIZED, TWISTED, 14 GAUGE WIRES AT 120° AROUND TREE. ATTACH TO TREE USING POLYPROPYLENE STRAPS. TENSION OF WIRES NOT TAUT TO ALLOW FOR SMALL AMOUNT OF TRUNK MOVEMENT. REMOVE AFTER ONE (1) YEAR.

ROOT COLLAR SHALL BE 2" HIGHER THAN THE ADJACENT FINISH GRADE. REMOVE EXCESS SOIL FROM TOP OF ROOT BALL.

1" OF HARDWOOD BARK MULCH OR APPROVED EQUAL. MULCH TO WITHIN 6" OF TRUNK/ COLLAR.

4' X 2" X 2" HARDWOOD STAKE 180° APART, DRIVEN FLUSH TO FINISH GRADE. TWO PER TREE.

REMOVE ALL TWINE, WIRE, ROPE, AND BURLAP FROM TOP \(\frac{3}{4} \) OF ROOT BALL. REMOVE ALL NON-ORGANIC MATERIAL FROM ENTIRE BALL. FOR WIRE BASKETS, CUT TOP AND FOLD DOWN IN THE PIT AFTER POSITIONED AND READY FOR BACKFILL. REFER TO CSI 32 92 00 - 5 FOR BALLED AND BURLAP PREPARATION AND REMOVAL. BACK FILL USING EXCAVATED TOPSOIL, OR SPECIFIED SOIL MIX. WATER THOROUGHLY TO ELIMINATE AIR POCKETS. BACKFILL SHOULD BE COMPACTED LIGHTLY. BACKFILL SHALL NOT BE COMPACTED TO A DENSITY THAT INHIBITS ROOT GROWTH. LOOSEN SIDE OF PLANTING HOLE AS PER ANSI Z60.1 STANDARD.

NOTES

- 1. NYLON, SYNTHETIC, OR TREATED BURLAP IS UNACCEPTABLE.
- 2. ALL PLANTING SHALL CONFORM TO APPLICABLE PARTS OF ANSI A300 (PART 6) AND THE ASSOCIATED BMP PUBLICATION. WHERE CONFLICT EXISTS BETWEEN THE PENN STANDARDS AND THE ANSI STANDARDS EXISTS, DEFER TO PENN STANDARDS.
- 3. UTILIZE URBAN-TOLERANT, PRIMARILY NATIVE TREES, SHRUBS, AND PERENNIALS. CONSIDER CLIMATE CHANGE IN SPECIES SELECTION.

EVERGREEN TREE PLANTING

SCALE: 1/4"=1'-0"

CSI 32 92 00 - 2

PLANTING - EVERGREEN TREE

LANDSCAPE STANDARDS



PRIOR TO CONSTRUCTION, CONFIRM LAYOUT, DIMENSIONS ADJACENT UTILITIES AND FINAL MATERIALS WITH U OF P OFFICE OF THE UNIVERSITY ARCHITECT. THIS DETAIL TO BE USED AS A GUIDE ONLY. SPECIFIC REVISIONS FOR SITE CONDITIONS AND INTENT ARE THE RESPONSIBILITY OF THE INDIVIDUAL PROJECT DESIGNER

> Facilities & Real Estate Services Office of the University Architect