



ASPHALT PAVING: SECTION

SCALE: 1-1/2"=1'-0"

NOTE:

1. BITUMINOUS PAVEMENTS MUST CONFORM TO PENNDOT STANDARDS.
2. COMPACT SUBGRADE PRIOR TO PAVEMENT INSTALLATION. DO NOT INSTALL BELOW 40°F OR ON WET SURFACES. OBTAIN MIXTURES FROM SOURCES ENSURING A UNIFORM FINISHED PRODUCT.
3. USE STEEL-WHEEL AND PNEUMATIC-TIRE ROLLERS UPON APPLICATION. SEALERS FOR CRACKS, SEAMS, AND PATCHES TO FOLLOW EMULSIFIED ASPHALT CLASS E-8 SEC 702.

CSI 32 14 23 - 2

ASPHALT PAVING

LANDSCAPE STANDARDS

PRIOR TO CONSTRUCTION, CONFIRM LAYOUT, DIMENSIONS, ADJACENT UTILITIES AND FINAL MATERIALS WITH U OF P OFFICE OF THE UNIVERSITY ARCHITECT. THIS DETAIL TO BE USED AS A GUIDE ONLY. SPECIFIC REVISIONS FOR SITE CONDITIONS AND INTENT ARE THE RESPONSIBILITY OF THE INDIVIDUAL PROJECT DESIGNER.